



Commercial Cooking Gas Parts Valves

7000 Series Gas Valve

The Robertshaw® 7000 Series Gas Valve is a combination gas valve that typically includes pilot safety valve, main gas regulation and main gas control. It is available for nearly any application. Multiple inlet and outlet sizes and orientations, multiple BTU capacity options, types of actuators, available inlet/outlet pressure taps along with pilot outlets make this the most versatile valve platform available

Popular used variety of commercial cooking equipment eg. Commercial ovens & fryers

Part No / Uline No	Inlet/Outlet	Pressure Setting
7000-BMVR-LP / (700-515) Rating: 250mV~750mV Reducer Bushings Included 2pcs. 3/4" x 1/2" Capacity: 485,000 BTU	3/4" x 3/4"	10.0" W.C (LP)
7000-BMVR-NAT (700-506 & 508) Rating: 250mV~750mV Reducer Bushings Included 2pcs. 3/4" x 1/2" Capacity: 300,000 BTU	3/4" x 3/4"	3.5" W.C (NAT)

Part No / Uline No	Inlet/Outlet	Pressure Setting
7000 BGOR-LP / (700-508) Rating: 250mV~750mV Bleed Gas Valve Control Reducer Bushings Included 2pcs. 3/4" x 1/2" Capacity: 485,000 BTU	3/4" x 3/4"	10.0" W.C (LP)

Part No / Uline No	Inlet/Outlet	Pressure Setting
7000-BE & 7000-BER / (700-402) UNI-KIT- model are suitable either for Natural Or LP Gas. A regulator cover Plate is included to convert to LP gas 24 Volt Combination Gas Valve Rating: 24V AC @ 0.2 Amps, 50/60 Hz 12V DC @ 0.18 Amps Side Outlet: 2 x 1/2" Reducer Bushing Included 1pc. 3/4" x 1/2" & 2pcs. 1/2" Plug Capacity: 300,000 BTU	1/2" x 3/4"	3.5" W.C (NAT) (Factory setting)



REACH ELECTRICAL (S) PTE LTD

51 Ubi Ave 1, #03-05, Paya Ubi Industrial Park, Singapore 408933

Tel: (65) 6296 6860 Fax: (65) 6298 1443

Email: reach@singnet.com.sg Website: <http://www.reachelectrical.com>

Company's Reg. No. : 199004352W G.S.T Reg. No. M2-0095215-4

Part No / Uline No.	Inlet/Outlet	Pressure Setting
7000BER-240 / (700-464) Rating: 240V AC @ 0.017 Amps, 50/60 Reducer Bushing Included 2pcs. $\frac{3}{4}$ " x $\frac{1}{2}$ " 3 Position Outlet Straight-Thru (FPT) 3 Position Outlet Side (FPT) with Plugs Capacity: 300,000 BTU	3/4" x 3/4"	3.5" W.C (NAT)



Part No / Uline No.	Inlet/Outlet	Pressure Setting
7000DERHC-S7C / (700-059) For D Pilot Ignition System Rating: 24V AC @ Hz 50/60 Reducer Bushing Included 2pcs. 1" x $\frac{3}{4}$ " Has "Slow Opening" Feature for Soft Ignition, Can be field Removed Suitable for all Nat. Gas 4.0" W.C. Capacity: 720,000 BTU	1" x 1"	4.0" W.C (NAT)



Part No / Uline No.	Inlet/Outlet	Pressure Setting
7000BDER-S7A / (700-056) For D Pilot Ignition System Rating: 24V AC @ Hz 50/60 Reducer Bushing Included 2pcs. $\frac{3}{4}$ " x $\frac{1}{2}$ " Has "Slow Opening" Feature for Soft Ignition, Can be field Removed Capacity: 300,000 BTU	3/4" x 3/4"	3.5" W.C (NAT)



REACH ELECTRICAL (S) PTE LTD

51 Ubi Ave 1, #03-05, Paya Ubi Industrial Park, Singapore 408933

Tel: (65) 6296 6860 Fax: (65) 6298 1443

Email: reach@singnet.com.sg Website: <http://www.reachelectrical.com>

Company's Reg. No. : 199004352W G.S.T Reg. No . M2-0095215-4